



STAINLESS STEEL FILTER

- GE SERIES -

GE 3 MODEL

IT	ENG	FR	
----	-----	----	--

COLLETTORE	CHAMBER	COLLECTEUR	
Materiale (Su richiesta)	Material (On request)	Matériel (Sur demande)	AISI 304 (AISI 316)
Pressione di lavoro (max.)	Working pressure (max.)	Pression de travail (max.)	10 bar
N. 1 o-ring di ricambio	No. 1 spare o-ring	N. 1 o-ring de rechange	●
N. 1 chiave per griffe	No. 1 wrench for claws	N. 1 clef pour agrafes	●
Scarico / sfiato 1/2" M - 1/4" F	Drain / Vent 1/2" M - 1/4" F	Soupirail / décharge 1/2" M - 1/4" F	●
Valvola di scarico / sfiato 1/2" - 1/4"	Drain / Vent valve 1/2" - 1/4"	Vanne de soupirail / décharge 1/2" - 1/4"	Optional
N. 2 manometri 0-16, Ø 50 inox	No. 2 S/S pressure gauges 0-16 Ø 50	N. 2 manomètres 0-16 Ø 50 inox	Optional
Predisposizione per trattamento acqua calda	Disposition for treatment of hot water	Disposition pour traitement d'eau chaude	Optional
Trattamento anticorrosivo per acqua di mare	Anti-corrosion internal treatment for sea-water	Traitement anticorrosif pour eau de mer	Optional

GE 3/35	GE 3/35	GE 3/35
Portata: 50 m ³ /h	Flow-rate: 50 m ³ /h	Débit: 50 m ³ /h
Raccordi IN/OUT: 3" M (*)	IN/OUT connections: 3" M (*)	Raccords IN/OUT: 3" M (*)
Cartucce : n. 3 mod CX 35 - AISI 316L in dotazione: Filtrazione 50 µm Superficie filtrante: 3.060 cm ²	Cartridges : n. 3 mod. CX 35-AISI 316L included: Filtration 50 µm Filtering surface: 3.060 cm ²	Cartouches : n. 3 mod. CX 35 - AISI 316L inclus: Filtration 50 µm Surface filtrante: 3.060 cm ²

GE 3/70	GE 3/70	GE 3/70
Portata: 95 m ³ /h	Flow-rate: 95 m ³ /h	Débit: 95 m ³ /h
Raccordi IN/OUT: 4" M (*)	IN/OUT connections: 4" M (*)	Raccords IN/OUT: 4" M (*)
Cartucce : n. 3 mod CX 70 - AISI 316L in dotazione: Filtrazione 50 µm Superficie filtrante: 6.360 cm ²	Cartridges : n. 3 mod. CX 70-AISI 316L included: Filtration 50 µm Filtering surface: 6.360 cm ²	Cartouches : n. 3 mod. CX 70 - AISI 316L inclus: Filtration 50 µm Surface filtrante: 6.360 cm ²

GE 3/100	GE 3/100	GE 3/100
Portata: 120 m ³ /h	Flow-rate: 120 m ³ /h	Débit: 120 m ³ /h
Raccordi IN/OUT: DN100 - PN10	IN/OUT connections: DN100 - PN10	Raccords IN/OUT: DN100 - PN10
Cartucce : n. 3 mod CX 100 - AISI 316L in dotazione: Filtrazione 50 µm Superficie filtrante: 9.195 cm ²	Cartridges : n. 3 mod. CX 100 - AISI 316L included: Filtration 50 µm Filtering surface: 9.195 cm ²	Cartouches : n. 3 mod. CX 100 - AISI 316L inclus: Filtration 50 µm Surface filtrante: 9.195 cm ²

Optional: 150-300 µm	Optional: 150-300 µm	Optional: 150-300 µm
-----------------------------	-----------------------------	-----------------------------

(*) UNI EN ISO 228-1:2003