

# GEL TERMOL AT

## Atoxic antifreeze

### Description

Gel Termol AT is an antifreeze, atoxic, colourless, concentrated and inhibited heat transfer fluid protecting against freezing in heating systems, solar panels and cooling circuits.

It is a highly technical product, formulated with high quality raw materials and with special long lasting inhibitors that prevent corrosion for years.

Because of the very low toxicity when swallowed (LD50 = 33 g / Kg of body weight), product is safely used in cooling circuits of systems, for processing food substances (wine, beer, frozen meat) and in all those cases where the fluid can accidentally come into contact with food.

### Use and dosage

When used as an antifreeze fluid, Gel Termol AT is diluted depending on the degree of protection required.



### BENEFITS

- Concentrated product to be diluted depending on protection required
- Easy to use
- No corrosion even after many years
- Atoxic product
- Safe to use in food industry

Protection temperature	Water %	Gel Termol AT %
-10°C	75	25
-15°C	67	33
-22°C	60	40
-33°C	50	50

Product is directly mixed with the system water in a variable percentage according to the table. It does not undergo degradation over time, maintaining its characteristics unchanged for many years, but it is recommended to periodically check concentration. For systems treated with different products, it is always recommended to empty the system and rinse it before using Gel Termol AT.

### Storage

Product remains stable for a long time if stored away from strong oxidants. Store product in a well ventilated place. Keep out of reach of children.

### Warnings

Gel Termol AT is an atoxic product and can be used in systems where there is a risk, even accidental, of contact with food substances. In case of contact with skin, wash the affected parts with soap and water.

**The above indications are based on our experience for general conditions of use and do not engage the responsibility of the supplier on the performances obtained which depend on water features, type of system and correct operation and maintenance.**

### Packaging

Gel Termol AT is available in the pack sizes below:  
 Kg 25 drum—Item Code 111.010.32  
 Kg 10 drum—Item Code 111.010.50