

FOLEO RESIDENTIAL SOFTENER

DESCRIPTION

The Foleo softener is available in 4 different sizes, in order to cover a wide range of residential applications. Its modern and attractive design competes with its premium performance.

TECHNICAL FEATURES

- Available in 10L, 15L, 20L as well as 30L versions.
- Equipped with the Fleck 5800 valve and the performant XTR touchscreen timer.
- The brine tank and the water tank are separated, for an eased maintenance and cleaning of the system.

ADDITIONNAL TECH CHARACT.

- Peak flow rate (m³/h): 1; 1.5; 2; 2.8
- Exchange capacity (°f m³): 48.4; 72.6; 96.8; 135.52
- Salt consumption / regen (kg): 0.8; 1.2; 1.6; 2.2
- Dimensions (WxLxH) mm: **10-15L** 360 x 456 x 750
20-30L 360 x 456 x 1045
- Connection size 1"



COMMERCIAL BENEFITS

- The shape of the main cover is very handy and permits a safer and more comfortable handling during installation.
- The maintenance is simplified thanks to the large opening, which gives a direct access to the valve.

TECHNICAL CHARACTERISTICS

- Sizes: 10, 15, 20, 30L
- Nominal flow rate (m³/h): 0.72; 1.08; 1.44; 2.02
- Integrated bypass: yes
- Integrated disinfection system

STYLE

Refined look made by **award-winning** industrial designer

HANDY

Removable salt compartment for an eased maintenance and cleaning of the system

PREMIUM

Touchscreen Fleck 5800 XTR valve with an upflow, variable brining capabilities to save about -50% on the water and salt savings